

Please cancel claims 1-27, without prejudice or disclaimer, and amend the remaining claims to read as follows:

29. (Amended) Device according to claim 28, wherein the CAN-system forms part of a machine-control system and/or a process-control system in which a first signal development obtains between the modules in the system for the performance of the particular process of the control system, and in that a first activation of the radiocommunication equipment means at the first location gives rise to a second activation of circuits in the second module, and in that the second activation gives rise to the signal activation in the second module.

30. (Amended) Device according to claim 29, wherein the signal activation caused by the second activation gives rise to a message initiation in the second module, which

prepares for a message transmission via a communication circuit of the module over the connection to the first module.

31. (Amended) Device according to claim 30, wherein the second module transmits the generated message according to a predetermined order of priority in the ordinary exchange of messages or signals between the first and second modules.

32. (Amended) Device according to claim 31, wherein the second module causes an interruption in the ordinary exchange of messages or signals within the CAN-system, and in that the signal activation in the second module, initiated by the second activation, takes charge of a generation and dispatch via a communication circuit, the connection to the first module, of one or more test messages.

33. (Amended) Device according to claim 32, wherein the second module, when a signal is activated on the basis of the second activation in the second module, imitates a control or supervisory function., which normally can occur in the machine and generates a supervisory control operation which is especially cut out for a testing or fault-searching function.

34. (Amended) Device according to claim 28, wherein the radiocommunication equipment means operates with two-way connections such that a stimulation of a controlled or supervised component at the first module produces a feedback from the first module via the connection to the second module, whereby an information signal representing the stimulation is generated, which information signal is transferred to the radio part situated at the second module, information which is transferred in this way via the radiocommunication equipment means being indicated or presented on or at the radiocommunication equipment means at the first module.

35. (Twice-amended) Device according to claim 28, wherein the equipment parts can observe and register the operation of input and output devices.

36. (Amended) Device according to claim 28, wherein the radiocommunication equipment means operates at high frequencies, e.g. frequencies of 2.4 GHz or more.

37. (Amended) Device according to claim 28, wherein the radiocommunication equipment means part at the first module is connected to a control or supervisory equipment part served by the first module.

38. (Amended) Device in a CAN-system (standard ISO 11898), comprising modules which can be connected via a digital serial communication connection and a first module means, and/or equipment unit(s) controlled by this, for observing or registering, at a location, the placement(s) of the first module means and/or of the equipment unit(s), characterized in that a radiocommunication equipment means for connection with a radio part belonging to a second module in the system for the establishment of a radiocommunication channel between the location and another location for the placement of the second module, and in that at the location the equipment unit(s) of the first module means can be stimulated by electrical and/or manual stimulation and the stimulation initiates the transmission of a message generated or present in the first module means over the connection to the second module, and in that the message hereupon induces activation of the radiocommunication equipment means and transfer of an item of information responding to the stimulation to an information-supplying unit, which delivers the information in question.

39. (Amended) Device according to claim 38, wherein the information makes it possible for a user to decide upon the relationship between the stimulation and the information.